

Inhaltsverzeichnis

UFW Firewall	1
<i>Installation</i>	1

UFW Firewall

Installation

[iptables2](#) ist eine Firewall Einrichtungen bei Ubuntu oder Debian. Eine vereinfachte Version ist [ufw](#) .

```
sudo apt-get update // Software update starten.
sudo -s // root Rechte erlangen, Sie müssen das root Passwort eingeben.
apt-get install ufw // Startet die Installation von ufw
```

Mit folgendem Befehl lässt sich die Einstellungen der Firewall anzeigen lassen.

```
ufw status // Beispielausgabe:

root@HPGen10-1:~# ufw status
Status: active

To Action From
-- -- --
OpenSSH ALLOW Anywhere
22/tcp ALLOW Anywhere
OpenSSH (v6) ALLOW Anywhere (v6)
22/tcp (v6) ALLOW Anywhere (v6)

root@HPGen10-1:~#
```

Die Einstellungen werden in folgenden drei Dateien gespeichert:

1. `/etc/ufw/before.rules`
2. `/var/lib/ufw/user.rules` (oder `/lib/ufw/user.rules` - in welche auch die in der Kommandozeile definierten Regeln persistiert werden)
3. `/etc/ufw/after.rules`

Diese Dateien lassen sich mit jedem Texteditor wie zum Beispiel [nano](#) verwalten. Hier eine Beispielausgabe der Datei: `/etc/ufw/before.rules`

```
root@HPGen10-1:~# root@HPGen10-1:~# cat /etc/ufw/before.rules
#
# rules.before
#
# Rules that should be run before the ufw command line added rules. Custom
# rules should be added to one of these chains:
#   ufw-before-input
#   ufw-before-output
#   ufw-before-forward
#
# Don't delete these required lines, otherwise there will be errors
```

```
*filter
:ufw-before-input - [0:0]
:ufw-before-output - [0:0]
:ufw-before-forward - [0:0]
:ufw-not-local - [0:0]
# End required lines

# allow all on loopback
-A ufw-before-input -i lo -j ACCEPT
-A ufw-before-output -o lo -j ACCEPT

# quickly process packets for which we already have a connection
-A ufw-before-input -m conntrack --ctstate RELATED,ESTABLISHED -j ACCEPT
-A ufw-before-output -m conntrack --ctstate RELATED,ESTABLISHED -j ACCEPT
-A ufw-before-forward -m conntrack --ctstate RELATED,ESTABLISHED -j ACCEPT

# drop INVALID packets (logs these in loglevel medium and higher)
-A ufw-before-input -m conntrack --ctstate INVALID -j ufw-logging-deny
-A ufw-before-input -m conntrack --ctstate INVALID -j DROP

# ok icmp codes for INPUT
-A ufw-before-input -p icmp --icmp-type destination-unreachable -j ACCEPT
-A ufw-before-input -p icmp --icmp-type time-exceeded -j ACCEPT
-A ufw-before-input -p icmp --icmp-type parameter-problem -j ACCEPT
-A ufw-before-input -p icmp --icmp-type echo-request -j ACCEPT

# ok icmp code for FORWARD
-A ufw-before-forward -p icmp --icmp-type destination-unreachable -j ACCEPT
-A ufw-before-forward -p icmp --icmp-type time-exceeded -j ACCEPT
-A ufw-before-forward -p icmp --icmp-type parameter-problem -j ACCEPT
-A ufw-before-forward -p icmp --icmp-type echo-request -j ACCEPT

# allow dhcp client to work
-A ufw-before-input -p udp --sport 67 --dport 68 -j ACCEPT

#
# ufw-not-local
#
-A ufw-before-input -j ufw-not-local

# if LOCAL, RETURN
-A ufw-not-local -m addrtype --dst-type LOCAL -j RETURN

# if MULTICAST, RETURN
-A ufw-not-local -m addrtype --dst-type MULTICAST -j RETURN

# if BROADCAST, RETURN
-A ufw-not-local -m addrtype --dst-type BROADCAST -j RETURN
```

```
# all other non-local packets are dropped
-A ufw-not-local -m limit --limit 3/min --limit-burst 10 -j ufw-logging-deny
-A ufw-not-local -j DROP

# allow MULTICAST mDNS for service discovery (be sure the MULTICAST line
above
# is uncommented)
-A ufw-before-input -p udp -d 224.0.0.251 --dport 5353 -j ACCEPT

# allow MULTICAST UPnP for service discovery (be sure the MULTICAST line
above
# is uncommented)
-A ufw-before-input -p udp -d 239.255.255.250 --dport 1900 -j ACCEPT

# don't delete the 'COMMIT' line or these rules won't be processed
COMMIT
root@HPGen10-1:~#
```

From:

<https://jmz-elektronik.ch/dokuwiki/> - Bücher & Dokumente

Permanent link:

<https://jmz-elektronik.ch/dokuwiki/doku.php?id=start:linux:ubuntu:ufw&rev=1593434479>

Last update: 2020/06/29 14:41

